

FSC Certified Particleboard Core

Positive Pressure	5 or 7-Ply
Thickness	Non-Rated: 1¾" standard • 1-3/8" available upon request Up to 20 Minute: 1¾" only
Maximum Sizes	Up to 20 Minute: Single 4° x 9° Pairs 8° x 9° Non-Rated: Single 4° x 10° Pairs 8° x 10°
CERTIFIED Core	100% FSC particleboard core with chain of custody certification. Core contains no added formaldehyde and is made from 100% pre-consumer recycle material. Graded to the ANSI A 208.1, Grade LD-2 specification for door core, the panel has an average density of 32lb. per cubic foot.
CERTIFIED Stiles	Minimum width 1¼" unless otherwise specified. ^{(1) (6)} Edge banding available
CERTIFIED Rails	Minimum width 2¼" unless otherwise specified. ⁽²⁾
Faces	All commercially available FSC certified veneers per AWI 1300, G11. 1/50" minimum veneer thickness, Medium Density Overlay (MDO), Hardboard ⁽³⁾
Core Assembly Adhesive	Type 1 —Waterproof Bond
Face Assembly Adhesive	Type 1 —Waterproof Bond
Core Bonding	Stiles and rails are securely bonded utilizing type 1 adhesive in conjunction with superior RF bonding technology. To ensure freedom from telegraphing of core components, the core unit is then sanded before face veneers are applied. Both hot press and cold press assembly available.
Warranty ⁽⁴⁾	Interior Use —Life of installation ⁽⁴⁾ Exterior Use —No Warranty
Standards	Meet or Exceed: WDMA I.S. 1-A-04 AWI Section 1300 PC-5 or PC-7 WI Section 12 Architectural Wood Doors—Flush UBC7-2-1997 UL10C WH/ITS Labeling Service
Light Openings	Non-Rated and up to 20 Minute Rated available. Light Openings are allowed. Visible glass and maximum opening dimensions depend on glazing options. Light cut-out shall be located a minimum of 5" from edge of door or any other cut-out (wire glass). Consult factory for glazing options and requirements.
Factory Finish	AWI system TR-6 > Clear > Standard color selections > Custom color matching ⁽⁵⁾
Factory Machining	> Pre-fitting > Templated hardware prep > Lite cutouts > Louver cutouts
LEED Credits Available	MR 5.1 & 5.2 Local and Regional Materials —project must be within 500 miles of Oregon Door manufacturing site (2 points possible) MR 4.1 & 4.2 Recycle Content 85% Pre-consumer 0% Post-consumer (2 points) MR 7 Certified Wood (1 point) FSC certificate # SCS-COC-000588 EQ 4.4 Low Emitting Material (1 point)



- (1) Compatible hardwood edges as specified for use with stain grade face veneers. Compatible hardwood or softwood edges available for use with paint grade faces.
- (2) Laminated Strand Lumber (LSL) or softwood rails at factory option, Wider rail available.
- (3) Hardboard available in 3-ply construction only.
- (4) See complete Oregon Door Limited Door Warranty for details.
- (5) Set-up fee for custom matching applies. Approval of custom samples is required prior to finishing
- (6) Standard stile construction is laminated hardwood or LSL backer with a maximum ¼" outer matching or compatible edge. Sizing and beveling should be done at the factory.