Oregon Door

FSC-SCL-5
FSC-SCL-7

FSC Certified
Structural Composite Lumber Core

Positive Pressure	5 or 7-Ply
Thickness	**Non-Rated** 1¾" standard 1-3/8" available upon request **Up to 20 Minute** 1¾" only
Maximum Sizes	**Up to 20 Minute** Single 4° x 9° Pairs 8° x 9° **Non-Rated** Single 4° x 10° Pairs 8° x 10°
Core	100% FSC Certified Structural Composite Lumber (core contains no added formaldehyde)
Edges	**Stiles:** FSC Certified minimum width 1¼ " unless otherwise specified. (1) **Rails:** FSC Certified Structural Composite Lumber Core
Edge Construction	**Category A:** Integral intumescent edge construction available. (Not Standard)
Faces	All commercially available veneers per AWI 1300, G11. 1/50" minimum veneer thickness, Medium Density Overlay (MDO), Hardboard (2)
Core Assembly Adhesive	**Type 1**—Waterproof Bond
Face Assembly Adhesive	**Type 1**—Waterproof Bond
Core Bonding	Stiles are securely bonded utilizing type 1 adhesive in conjunction with superior RF bonding technology. To ensure freedom from telegraphing of core components, the core unit is then sanded before face veneers are applied.
Warranty (3)	**Interior Use**—Life of installation **Exterior Use**—No Warranty(5)
Standards	**Meet or Exceed:** WDMA I.S. 1-A-04 (meets WDMA "Extra Heavy-Duty" standards) AWI Section 1300 PC-5 or PC-7 WI Section 12 Architectural Wood Doors—Flush UBC7-2-1997 UL10C WH/ITS Labeling
Light Openings	Non-Rated and up to 20 Minute Rated available. Light Openings are allowed. Visible glass and maximum opening dimensions depend on glazing options. Light cut-out shall be located a minimum of 5" from edge of door or any other cut-out (wire glass). Consult factory for glazing options and requirements.
Factory Finish	AWI system TR-6 > Clear > Standard color selections > Custom color matching (4)
Factory Machining	> Pre-fitting >Templated hardware prep > Lite cutouts > Louver cutouts
LEED Credits Available	**MR 5.1 & 5.2 Local and Regional Materials**—project must be within 500 miles of final assembly point in Dillard Oregon (2 points possible) **EQ 4.4 Low Emitting Materials** (1 point) **MR7 Certified Wood** (1 point) FSC certificate # SCS-COC-000588

(1) Compatible hardwood edges as specified for use with stain grade face veneers. Compatible hardwood or softwood edges available for use with paint grade faces.
(2) Hardboard available in 3-ply construction only.
(3) See complete Oregon Door Limited Door Warranty for details.
(4) Set-up fee for custom matching applies. Approval of custom samples is required prior to finishing.
(5) Consult factory for possible 2-year exterior warranty. Additional conditions may apply.

PO Box 1960 • Winston, OR 97496 • 800/722-7269 • Fax 541/679-5063 • oregondoor.com